

Description

The new fixed and adjustable E5™ and established E8™ fixed and adjustable fire rated downlights set new levels in performance. Featuring the sparkling low glare multifaceted EnFiniti™ lens and delivering up to 380lm from 4.5W version and 595lm from 8W. The E5™ and E8™ are packed with features and benefits which allow for a quick and cost effective installation while still providing users with optimum performance and energy saving LED technology. Tested in 30, 60 and 90-minute fire rated ceilings.

4.5W/8W up to 595 Lumens
L70 25,000 Hours

E5 & E8 AVAILABLE IN FIXED & ADJUSTABLE VERSIONS

Features & Benefits

- EnFiniti™ edge-to-edge multifaceted polycarbonate lens for low glare and halogen like appearance
- Wide 60° beam angle delivers increased light distribution
- Fibre based insulation coverable - up to 250mm
- Integrated driver with push fit loop in/out terminals suitable for use with solid or stranded cable for easy installation
- Super slim interchangeable bezels for fixed version provide a high end sleek finish. Bezel included with adjustable version.
- Community Design Registrations for E5™ and E8™
- BS EN 1365-2: 2014 (Fire resistance)
- BS EN ISO 10140-2: 2010 & BS EN ISO 10140-3: 2010 + A1: 2015 (Acoustics)
- BS EN 13141-1:2004 (Air leakage) - excluding adjustable version
- 3 year warranty



EN-DE5
E5 Fixed 4.5W Dimmable IP65
Fire Rated LED Downlight

EN-DE52
E5 Adjustable 4.5W Dimmable IP20
Fire Rated LED Downlight

EN-DE8
E8 Fixed 8W Dimmable IP65
Fire Rated LED Downlight

EN-DE82
E8 Adjustable 8W Dimmable IP20
Fire Rated LED Downlight

Cat. No.	Watts	Beam	Colour	Lumens	lm/W	L70 Life (hrs)	Horz. Adj.	Overall [Ø]	Cutout [Ø]	Recess	Subst.
E5™ DIMMABLE FIXED											
EN-DE5/30	4.5W	60°	3000K	355lm	79	25,000	-	78mm	60mm	69mm	35W
EN-DE5/40	4.5W	60°	4000K	380lm	84	25,000	-	78mm	60mm	69mm	35W
E5™ DIMMABLE ADJUSTABLE											
EN-DE52*/30	4.5W	60°	3000K	370lm	82	25,000	20°	88mm	75mm	90mm	35W
EN-DE52*/40	4.5W	60°	4000K	390lm	87	25,000	20°	88mm	75mm	90mm	35W
E8™ DIMMABLE FIXED											
EN-DE8/30	8W	60°	3000K	565lm	71	25,000	-	85mm	70mm	90mm	50W
EN-DE8/40	8W	60°	4000K	565lm	71	25,000	-	85mm	70mm	90mm	50W
E8™ DIMMABLE ADJUSTABLE											
EN-DE82*/30	8W	60°	3000K	595lm	74	25,000	20°	98mm	80mm	110mm	50W
EN-DE82*/40	8W	60°	4000K	595lm	74	25,000	20°	98mm	80mm	110mm	50W

ACCESSORIES

- EN-BZE5* E5 Fixed IP65 Aluminium Downlight Bezel
- EN-BZE8* E8 Fixed IP65 Aluminium Downlight Bezel

*Add suffix **W**, **MW**, **PC** or **SN** for White, Matt White, Polished Chrome or Satin Nickel finishes.
3 hour Emergency pack **AU-FRLM10EM** available.

Finish Options:



Technical Information

Ra >80
COLOUR RENDERING



CB



ErP
COMPLIANT

